

View Online at <https://aerobasegroup.com/nsn/3110-01-055-3945>

**Shank Diameter:**

Between 0.6230 inches and 0.6250 inches

**Shank Style:**

Hollow

**Overall Length:**

2.0930 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Overall Outside Diameter:**

Between 0.9280 inches and 0.9480 inches

**Lubrication Material:**

Grease

**Outer Ring Width:**

Between 0.4280 inches and 0.4480 inches

**Inner Ring Width:**

Between 0.5880 inches and 0.5930 inches

**Length From Bore Center To Shank End:**

Between 1.6150 inches and 1.6350 inches

**Shank Bore Diameter:**

Between 0.5156 inches and 0.5163 inches

**Shank Bore Depth:**

0.8750 inches

**Shield Quantity:**

2

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

Rivet hole 0.1250 in. Min diameter located 0.5000 in. From end of shank

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel rod end body

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Style Designator:**

Double row, staggered, ball

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.