

View Online at <https://aerobasegroup.com/nsn/3110-01-056-2975>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.4060 inches and 0.4680 inches

Overall Length:

Between 1.4390 inches and 1.5260 inches

Overall Outside Diameter:

Between 0.7490 inches and 0.7510 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.3110 inches and 0.3120 inches

Outer Ring Width:

Between 0.3390 inches and 0.3440 inches

Stud Length:

Between 1.0940 inches and 1.1560 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Special Features:

Nas516 lubricator in roller end, cotter pin hole 0.076 in. Diameter located 0.109 in. From end of stud

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100 stud or steel comp 8620 stud or steel comp 8720 stud or steel comp 4620 stud or steel comp 8620h stud

Material Specification:

Mil-s-7420 military specification all material responses roller

Surface Treatment:

Cadmium end plate

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response stud

Style Designator:

Cam follower

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.