

View Online at <https://aerobasegroup.com/nsn/3110-01-074-3909>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.4370 inches

Overall Length:

Between 1.8000 inches and 1.8777 inches

Overall Outside Diameter:

Between 1.1245 inches and 1.1260 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.6240 inches and 0.6250 inches

Outer Ring Width:

Between 0.6200 inches and 0.6250 inches

Stud Length:

Between 1.1590 inches and 1.2060 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Special Features:

Od crowned on a 10 in. Radius; 10 pct molybdenum disulfide lubricant, 81755, fms-0169; nas516-1 lubrication fitting in stud end

Lubrication Material Specification:

Mil-g-25760 military specification single material response

Material:

Steel outer ring

Material Specification:

Vasscomax 350 cvm, fscm 87665 mfr ref single material response outer ring

Surface Treatment:

Cadmium exposed surfaces as mounted

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response exposed surfaces as mounted

Style Designator:

Cam follower

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-25760 spec.