Needle Bearing Cam Follower - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-01-074-6915

View Online at https://aerobasegroup.com/nsn/3110-01-074-6915
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.2840 inches
Overall Length:
Between 1.3490 inches and 1.4260 inches
Overall Outside Diameter:
Between 0.4995 inches and 0.5010 inches
Lubrication Material:
Grease
Stud Diameter:
Between 0.2490 inches and 0.2500 inches
Outer Ring Width:
Between 0.3910 inches and 0.4210 inches
Stud Length:
Between 0.9580 inches and 1.0050 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Special Features:
Od crowned on a 10 in. Radius; 10 pct molybdenum disulfide, 81755, fms-0169; nas516-1 lubrication fitting on stud end
Lubrication Material Specification:
Mil-g-25760 military specification single material response
Material:
Steel comp e52100 stud
Material Specification:
66 federal standard single material response stud
Surface Treatment:
Cadmium exposed surfaces as mounted
Surface Treatment Specification:
Qq-p-416, type 1, cl 2 federal specification single treatment response exposed surfaces as mounted
Style Designator:
Cam follower
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Needle Bearing Cam Follower - Page 2 of 2



Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-25760 spec.