

View Online at <https://aerobasegroup.com/nsn/3110-01-095-7682>

Overall Width:

Between 0.1950 inches and 0.1960 inches

Bore Diameter:

Between 0.2498 inches and 0.2500 inches

Lubrication Material:

Grease

Flange Outside Diameter:

Between 0.6890 inches and 0.6900 inches

Flange Width:

Between 0.0020 inches and 0.0420 inches

Outer Ring Outside Diameter:

Between 0.6248 inches and 0.6250 inches

Surface Finish:

Ground

Retainer Fabrication Method:

Pressed

Shield Quantity:

2

Load Direction:

Radial

Bore Shape:

Straight

Internal Clearance:

0.0001 inches radial and 0.0008 inches radial

Standard Tolerance Designation:

Abec no. 5p

Special Features:

Stabilized for operation at 500 degrees f, packed 25 pct full w/lubricant

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel shield

Material Specification:

S313-13, 12511 mfr ref all material responses shield

Style Designator:

Non-loading groove, non-separable

Test Data Document:

12511-s313-13 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.