

View Online at <https://aerobasegroup.com/nsn/3110-01-134-2789>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

Between 0.1894 inches and 0.1900 inches

Shank Style:

Externally threaded

Overall Length:

3.9400 inches

Bore Diameter:

0.2500 inches

Overall Outside Diameter:

1.1200 inches

Lubrication Material:

Grease

Shank Thread Length:

0.5000 inches

Outer Ring Width:

Between 0.2190 inches and 0.2290 inches

Inner Ring Width:

0.2810 inches

Length From Bore Center To Shank End:

3.3800 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

80 pct full of specified lubricant

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp 630 rod end body

Material Specification:

Ams 5643 assn standard single material response rod end body

Surface Treatment:

Passivate rod end body

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response exposed surfaces as mounted

Style Designator:

Single row, ball

Test Data Document:

76301-ps21202, class a-d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.