

View Online at <https://aerobasegroup.com/nsn/3110-01-134-5871>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.3360 inches and 0.3760 inches

**Overall Length:**

Between 1.3180 inches and 1.3810 inches

**Overall Outside Diameter:**

Between 0.6245 inches and 0.6250 inches

**Lubrication Material:**

Grease

**Stud Diameter:**

Between 0.3105 inches and 0.3120 inches

**Outer Ring Width:**

Between 0.4280 inches and 0.4330 inches

**Stud Length:**

Between 0.8260 inches and 0.8730 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Special Features:**

80 pct full of specified lubricant; spherical od, 7.560 in. R; slot in bottom of shank, 0.066 in. Min and 0.072 in. Maximum w x 0.094 in. Min and 0.100 in. Maximum depth; cotter pin hole in shank

**Lubrication Material Specification:**

Mil-g-81322 military specification single material response

**Material:**

Steel comp 440c roller

**Material Specification:**

Ams 5630 assn standard single material response outer ring

**Surface Treatment:**

Passivate

**Style Designator:**

Cam follower

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-81322 spec.