

View Online at <https://aerobasegroup.com/nsn/3110-01-134-5871>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.3360 inches and 0.3760 inches

Overall Length:

Between 1.3180 inches and 1.3810 inches

Overall Outside Diameter:

Between 0.6245 inches and 0.6250 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.3105 inches and 0.3120 inches

Outer Ring Width:

Between 0.4280 inches and 0.4330 inches

Stud Length:

Between 0.8260 inches and 0.8730 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Special Features:

80 pct full of specified lubricant; spherical od, 7.560 in. R; slot in bottom of shank, 0.066 in. Min and 0.072 in. Maximum w x 0.094 in. Min and 0.100 in. Maximum depth; cotter pin hole in shank

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp 440c roller

Material Specification:

Ams 5630 assn standard single material response outer ring

Surface Treatment:

Passivate

Style Designator:

Cam follower

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.