

View Online at <https://aerobasegroup.com/nsn/3110-01-147-8709>

**Cross Sectional Shape:**

Recessed w/ aperture

**Counterbore Diameter:**

0.688 inches

**Counterbore Depth:**

0.500 inches

**Outside Diameter:**

9.062 inches

**Minor Thickness:**

0.625 inches

**Recess Diameter:**

Between 8.252 inches and 8.254 inches

**Recess Depth:**

0.590 inches

**Mounting Hole Diameter:**

0.406 inches

**Aperture Diameter:**

Between 2.763 inches and 2.767 inches

**Mounting Hole Arrangement Style:**

Single bolt hole circle

**Bolt Circle Hole Quantity:**

8

**Overall Thickness:**

1.531 inches

**Mounting Bolt Circle Diameter:**

7.375 inches

**Raised Surface Height:**

Between 0.682 inches and 0.686 inches

**Mounting Hole Type:**

Round, unthreaded, counterbored

**Outside Raised Surface Diameter:**

Between 6.295 inches and 6.298 inches

**Special Features:**

Circumferential groove in face of raised surface 0.500 in. Dp, 0.656 in. Wd; cbore aperture 4.000 in. Dia, 0.906 in. Dp; two circumferential grooves in. Aperture id, 0.125 in. Wd, 0.063 in. Dp; four holes on 5.875 in. Diameter blt cir, 0.107 in. Diameter by 0.500 in. Dp, countersunk 0.188 in. Diameter by 60.0 deg., tap 0.138-32 unc 0.250 in. Dp; four holes in od of flanges, 0.250-20 unc tap by 0.375 in. Dp, equally spaced

**Material:**

Steel

**Material Specification:**

Emd 237, fscm 95402 mfr ref single material response

**Style Designator:**

Round

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A093a0