NSN 3110-01-167-2442

Annular Ball Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-01-167-2442

| Overall Width: |
|---|
| Between 0.1084 inches and 0.1094 inches |
| Bore Diameter: |
| Between 0.1560 inches and 0.1562 inches |
| Lubrication Material: |
| Oil |
| Flange Outside Diameter: |
| Between 0.3580 inches and 0.3590 inches |
| Flange Width: |
| Between 0.0210 inches and 0.0230 inches |
| Outer Ring Outside Diameter: |
| Between 0.3123 inches and 0.3125 inches |
| Surface Finish: |
| Ground |
| Load Direction: |
| Radial |
| Bore Shape: |
| Straight |
| Internal Fit-up Contact Angular Direction: |
| Primarily radial |
| Internal Clearance: |
| 0.0002 inches radial and 0.0006 inches radial |
| Standard Tolerance Designation: |
| Abec no. 5p |
| Lubrication Material Specification: |
| Mil-I-6085 military specification single material response |
| Material: |
| Steel comp 440c |
| Material Specification: |
| Qq-s-763 federal specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35, type 2 or type 5 or type 6 federal specification single treatment response |
| Style Designator: |
| Non-loading groove, non-separable |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 3110-01-167-2442

Annular Ball Bearing - Page 2 of 2



Fiig:

A044a0

Mil-std (military Standard):

Mil-I-6085 spec.