

View Online at <https://aerobasegroup.com/nsn/3110-01-173-3723>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Diameter:**

0.2500 inches

**Shank Style:**

651 externally threaded

**Overall Length:**

1.7620 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Overall Outside Diameter:**

Between 0.7500 inches and 0.8000 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 0.7500 inches and 0.8100 inches

**Outer Ring Width:**

Between 0.3350 inches and 0.3500 inches

**Inner Ring Width:**

Between 0.3700 inches and 0.3750 inches

**Length From Bore Center To Shank End:**

Between 1.3650 inches and 1.3950 inches

**Seal Quantity:**

1

**Shield Quantity:**

1

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Internal Clearance:**

0.0002 inches radial and 0.0010 inches radial

**Features Provided:**

Flush lubrication fitting

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.250 inches

**Self-alignment Angle:**

4.00 degrees

**Lubrication Material Specification:**

Mil-g-81322 military specification single material response

**Material:**

Steel comp e52100 roller

**Material Specification:**

Qq-s-763 federal specification single material response shield

**Surface Treatment:**

Cadmium exposed surfaces as mounted

**Surface Treatment Specification:**

Qq-p-416, type 1, class 2 federal specification single treatment response exposed surfaces as mounted

**Style Designator:**

Single row, concave rollers

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-81322 spec.