## NSN 3110-01-176-6402

Bearing Retaining Plate - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3110-01-176-6402

| Outside Diameter:  Between 3.360 inches and 3.380 inches  Minor Thickness:  0.0705 inches   |        |
|---|--------|
| Counterbored w/ aperture  Outside Diameter:  Between 3.360 inches and 3.380 inches  Minor Thickness:  0.0705 inches                 |        |
| Between 3.360 inches and 3.380 inches  Minor Thickness:  0.0705 inches  |        |
| Minor Thickness: 0.0705 inches  |        |
| 0.0705 inches   |        |
|   |        |
| Manustina Hala Diameter   |        |
| Mounting Hole Diameter:   |        |
| Between 0.296 inches and 0.303 inches   |        |
| Aperture Diameter:  |        |
| 2.953 inches  |        |
| Overall Thickness:  |        |
| Between 0.711 inches and 0.735 inches   |        |
| End Application:  |        |
| Aircraft eng f-101  |        |
| Hardness Rating:  |        |
| Between 26.0 rockwell c and 32.0 rockwell c   |        |
| Counterbore Diameter:   |        |
| Between 2.680 inches and 2.720 inches   |        |
| Counterbore Depth:  |        |
| Between 0.640 inches and 0.665 inches   |        |
| Mounting Hole Type:   |        |
| Round, unthreaded   |        |
| Special Features:   |        |
| Four tabs 0.660 in. Min 0.700 in. Maximum located on 4.440 dbc; magnetic particle insp per ams-2640; personnel qualification per mi | litary |
| standard 410 reqd; process shall be fluorescent and continuous w5 gauss maximum residual magnetism allowed                          |        |
| Material:   |        |
| Steel comp 4340   |        |
| Surface Treatment:  |        |
| Oxide   |        |
| Surface Treatment Specification:  |        |
| Ams-2485 assn standard single treatment response  |        |
| Shelf Life:   |        |
| N/a   |        |
| Unit Of Measure:  |        |
| <del></del>   |        |
| Demilitarization:   |        |
| No  |        |
| Fiig:   |        |
| A093a0  |        |