

View Online at <https://aerobasegroup.com/nsn/3110-01-180-9361>

Overall Width:

Between 0.5604 inches and 0.5624 inches

Bore Diameter:

Between 0.3748 inches and 0.3750 inches

Overall Outside Diameter:

Between 0.8748 inches and 0.8750 inches

Lubrication Material:

Grease

End Application:

5895-01-119-1601 recorder-reprocer, signal data

Surface Finish:

Ground

Retainer Fabrication Method:

Stamped

Shield Quantity:

2

Load Direction:

Radial

Internal Clearance:

0.0005 inches radial and 0.0008 inches radial

Standard Tolerance Designation:

Abec no. 7p

Bearing Preload Rating:

5.0 pounds

Lubrication Material Specification:

Mil-g-23827, a72832 military specification single material response

Material:

Steel comp 440c

Material Specification:

Mil-b-23063, calss 3 military specification single material response

Reference Data And Literature:

Mil-b-23063 class 3 except qualification

Style Designator:

92b counterbored outer rings, non-separable, back to back mounting

Type/model Designation:

Rd-450/ash-33

Specification Data:

28009-16610107 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.