

View Online at <https://aerobasegroup.com/nsn/3110-01-186-3508>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.3590 inches

Overall Length:

1.3340 inches

Overall Outside Diameter:

Between 0.8745 inches and 0.8760 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.3735 inches and 0.3750 inches

Outer Ring Width:

Between 0.4640 inches and 0.4690 inches

Stud Length:

0.8590 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Standard Tolerance Designation:

Afbma standard tolerance for can follwer needle bearing

Special Features:

Nas516-1 lubrication fitting in threaded end of stud

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel end plate

Material Specification:

Sae assn standard single material response stud

Surface Treatment:

Cadmium exposed surfaces of stud and washer as mounted

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response exposed surfaces of stud and washer as mounted

Style Designator:

Cam follower

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.