

View Online at <https://aerobasegroup.com/nsn/3110-01-186-5522>

Overall Width:

Between 0.8350 inches and 0.8450 inches

Bore Diameter:

Between 8.9993 inches and 9.0000 inches

Overall Outside Diameter:

Between 9.7493 inches and 9.7500 inches

Lubrication Material:

Oil

Surface Finish:

Ground

Retainer Fabrication Method:

Machined

Seal Quantity:

2

Bearing Seal Type:

Lips turned inwardly

Load Direction:

Angular

Internal Fit-up Designation:

Standard

Standard Tolerance Designation:

Abec no.3

Bearing Preload Rating:

Between 720.0 pounds and 880.0 pounds

Contact Angle:

30.0 degrees

Special Features:

Passivate, qq-p-35, rings and balls; 20 drops of specified lubricant fromno. 26 hypodermic needle

Lubrication Material Specification:

Mil-I-6085 military specification single material response

Material:

Steel comp 440c outer ring

Material Specification:

Mil-r-6855, class 2, type a military specification single material response seal

Style Designator:

92b counterbored outer rings, non-separable, back to back mounting

Specification Data:

58260-13084019 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A044a0

Mil-std (military Standard):

Mil-I-6085 spec.