

View Online at <https://aerobasegroup.com/nsn/3110-01-189-7567>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Diameter:**

0.3750 inches

**Shank Style:**

Externally threaded

**Overall Length:**

1.7660 inches

**Bore Diameter:**

Between 0.1897 inches and 0.1900 inches

**Overall Outside Diameter:**

Between 0.7710 inches and 0.7910 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 0.7190 inches and 0.7810 inches

**Outer Ring Width:**

Between 0.3180 inches and 0.3380 inches

**Inner Ring Width:**

Between 0.4320 inches and 0.4370 inches

**Length From Bore Center To Shank End:**

Between 1.3650 inches and 1.3850 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Internal Clearance:**

0.0000 inches radial and 0.0004 inches radial

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Standard Tolerance Designation:**

Abec no.1

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

Keyway in shank

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel comp 4720 rod end body or steel comp 8620 rod end body or steel comp 4130 rod end body

**Material Specification:**

Mil-s-7420 military specification single material response inner ring

**Surface Treatment:**

Cadmium exposed surfaces as mounted

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response exposed surfaces as mounted

**Style Designator:**

Double row, staggered, ball

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.