# NSN 3110-01-191-3230

Duplex Ball Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-01-191-3230

#### **Overall Width:**

Between 0.6040 inches and 0.6240 inches

#### Bore Diameter:

Between 3.0622 inches and 3.0625 inches

### **Overall Outside Diameter:**

Between 3.8746 inches and 3.8750 inches

#### Lubrication Material:

Oil

Surface Finish:

Ground

## **Retainer Fabrication Method:**

Pressed

#### Shield Quantity:

2

#### Load Direction:

-0

Angular

# Standard Tolerance Designation:

Abec no. 5t

## **Bearing Preload Rating:**

Between 90.0 pounds and 110.0 pounds

## **Contact Angle:**

Between 15.0 degrees and 25.0 degrees

#### **Special Features:**

Vacuum impregnate retainer with specified oil, centrifuge for 2 minutes at 100 g after vacuum; inscribe match mark on od of each bearing;

one shield each bearing

#### Lubrication Material Specification:

Mil-I-6085 military specification single material response

#### Material:

Stainless steel shield

#### **Material Specification:**

Mil-p-79, type fbe military specification single material response retainer

#### Style Designator:

92b counterbored outer rings, non-separable, back to back mounting

#### **Specification Data:**

82577-901861 manufacturers standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A044a0

# NSN 3110-01-191-3230

Duplex Ball Bearing - Page 2 of 2

# Mil-std (military Standard):

Mil-I-6085 spec.

