

View Online at <https://aerobasegroup.com/nsn/3110-01-191-6374>

Overall Width:

Between 0.2330 inches and 0.2340 inches

Bore Diameter:

Between 0.1873 inches and 0.1875 inches

Lubrication Material:

Oil and grease

Flange Outside Diameter:

Between 0.8690 inches and 0.8700 inches

Flange Width:

Between 0.0300 inches and 0.0320 inches

Outer Ring Outside Diameter:

Between 0.6248 inches and 0.6250 inches

Surface Finish:

Ground

Shield Quantity:

2

Alignment Type:

Rigid

Load Direction:

Radial

Bore Shape:

Straight

Internal Clearance:

0.0003 inches radial and 0.0005 inches radial

Special Features:

Consists of an inner single row of balls and an outer double row of balls; outer row retainers to be polytetrafluoroethylene tubing; lubrication of inner row to be 3 drops of specified oil with a no. 26 beck and dickenson hypodermic needle; lubrication outer row to 5.0 to 15.0 mg of specified grease

Lubrication Material Specification:

As2844, fscm 97424 mfr ref 1st material response and mil-g-23827 military specification 2nd material response

Material:

Steel outer ring

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.