

View Online at <https://aerobasegroup.com/nsn/3110-01-191-7541>

Overall Width:

Between 0.6050 inches and 0.6250 inches

Bore Diameter:

Between 4.4997 inches and 4.5000 inches

Overall Outside Diameter:

Between 5.1246 inches and 5.1250 inches

Lubrication Material:

Oil

Surface Finish:

Ground

Retainer Fabrication Method:

Pressed

Shield Quantity:

2

Load Direction:

Angular

Standard Tolerance Designation:

Abec no.5

Bearing Preload Rating:

Between 20.0 pounds and 30.0 pounds

Contact Angle:

Between 15.0 degrees and 25.0 degrees

Special Features:

Vacuum impregnated retainer with specified oil, centrifuge for 2 minutes at 100 g after vacuum; inscribe match mark on od of each bearing;

1 shield each bearing

Lubrication Material Specification:

Mil-I-6085 military specification single material response

Material:

Stainless steel shield

Material Specification:

Mil-p-79, type fbe military specification single material response retainer

Style Designator:

92b counterbored outer rings, non-separable, back to back mounting

Specification Data:

82577-801860 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-I-6085 spec.