

View Online at <https://aerobasegroup.com/nsn/3110-01-195-5147>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.4220 inches

Overall Length:

1.2815 inches

Overall Outside Diameter:

Between 0.9995 inches and 1.0010 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.4355 inches and 0.4370 inches

Outer Ring Width:

Between 0.5260 inches and 0.5310 inches

Stud Length:

0.7345 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

Standard Tolerance Designation:

Afbma standard tolerance for can follwer needle bearing

Special Features:

Lubricator in threaded end of stud, no cotter pin hole

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel end plate

Material Specification:

Sae assn standard single material response stud

Surface Treatment:

Cadmium end plate exposed surfaces

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response stud

Style Designator:

Cam follower

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.