

View Online at <https://aerobasegroup.com/nsn/3110-01-197-6653>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.3440 inches

**Overall Length:**

0.7560 inches

**Overall Outside Diameter:**

0.5000 inches

**Lubrication Material:**

Grease

**Stud Diameter:**

0.1900 inches

**Outer Ring Width:**

0.2810 inches

**Stud Length:**

0.4690 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Rigid

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Standard Tolerance Designation:**

Afbma standard tolerance for can follwer needle bearing

**Special Features:**

Cotter pin hole in threaded end of stud, 0.100 in. From stud end, 0.070 in. Dia; no lubricator

**Lubrication Material Specification:**

Mil-g-81322 military specification single material response

**Material:**

Steel end plate

**Material Specification:**

Sae assn standard single material response stud

**Surface Treatment:**

Cadmium exposed surfaces of stud and washer as mounted

**Surface Treatment Specification:**

Qq-p-416, type 1, class 2 federal specification single treatment response exposed surfaces of stud and washer as mounted

**Style Designator:**

Cam follower

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas562 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-81322 spec.