

View Online at <https://aerobasegroup.com/nsn/3110-01-202-2746>

Overall Width:

Between 0.2350 inches and 0.2500 inches

Bore Diameter:

Between 0.2498 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.3748 inches and 0.3750 inches

Lubrication Material:

Lubricating oil

Surface Finish:

Ground

Shield Quantity:

2

Load Direction:

Radial

Bearing Preload Designation:

Medium

Internal Clearance:

0.0004 inches radial and 0.0008 inches radial

Standard Tolerance Designation:

Abec no. 5p

Bearing Preload Rating:

1.0 pounds

Special Features:

Electro etch marking on bearing od for assembly instructions

Lubrication Material Specification:

Mil-I-6085 federal specification single material response

Material:

Stainless steel

Material Specification:

Aisi 440c assn standard single material response outer ring

Style Designator:

92a non-loading groove, non-separable, tandem mounting

Supplementary Features:

Back to back configuration; cage type, crown, land piloted; double metal shield, removable; packaging, unit, duplex pairs

Specification Data:

50294-ssri-614zzdb1ha5+48lo2u manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-I-6085 spec.