

View Online at <https://aerobasegroup.com/nsn/3110-01-202-2746>

**Overall Width:**

Between 0.2350 inches and 0.2500 inches

**Bore Diameter:**

Between 0.2498 inches and 0.2500 inches

**Overall Outside Diameter:**

Between 0.3748 inches and 0.3750 inches

**Lubrication Material:**

Lubricating oil

**Surface Finish:**

Ground

**Shield Quantity:**

2

**Load Direction:**

Radial

**Bearing Preload Designation:**

Medium

**Internal Clearance:**

0.0004 inches radial and 0.0008 inches radial

**Standard Tolerance Designation:**

Abec no. 5p

**Bearing Preload Rating:**

1.0 pounds

**Special Features:**

Electro etch marking on bearing od for assembly instructions

**Lubrication Material Specification:**

Mil-I-6085 federal specification single material response

**Material:**

Stainless steel

**Material Specification:**

Aisi 440c assn standard single material response outer ring

**Style Designator:**

92a non-loading groove, non-separable, tandem mounting

**Supplementary Features:**

Back to back configuration; cage type, crown, land piloted; double metal shield, removable; packaging, unit, duplex pairs

**Specification Data:**

50294-ssri-614zzdb1ha5+48lo2u manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-I-6085 spec.