

View Online at <https://aerobasegroup.com/nsn/3110-01-202-6917>

Bore Diameter:

0.1250 inches

Lubrication Material:

Grease and oil

Flange Outside Diameter:

0.3590 inches

Flange Width:

0.0310 inches

Outer Ring Width:

0.1406 inches

Inner Ring Width:

0.1718 inches

Outer Ring Outside Diameter:

0.3125 inches

Surface Finish:

Ground

Retainer Fabrication Method:

Pressed

Shield Quantity:

2

Alignment Type:

Rigid

Load Direction:

Radial

Bore Shape:

Straight

Internal Clearance:

0.0005 inches radial and 0.0008 inches radial

Standard Tolerance Designation:

Abec no.3

Special Features:

Lubrication mixture 80.0 cc versilube f-50 and 10 grams versilube g-300

Lubrication Material Specification:

Versilube g-300, fscm 59317 mfr ref 1st material response and versilube f-50, fscm 59317 mfr ref 2nd material response

Material:

Stainless steel shield

Material Specification:

Aisi assn standard single material response outer ring

Style Designator:

Non-loading groove, non-separable

Specification Data:

73030-746435 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0