

View Online at <https://aerobasegroup.com/nsn/3110-01-210-3207>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.3440 inches

Overall Length:

1.1935 inches

Overall Outside Diameter:

Between 0.6870 inches and 0.6885 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.2485 inches and 0.2500 inches

Outer Ring Width:

Between 0.2760 inches and 0.2810 inches

Stud Length:

Between 0.8905 inches and 0.9375 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Special Features:

No plating on id of outer ring

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel end plate

Material Specification:

Sae assn standard single material response stud

Surface Treatment:

Cadmium exposed surfaces of stud and washer as mounted

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response exposed surfaces of stud and washer as mounted

Style Designator:

Cam follower

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.