

View Online at <https://aerobasegroup.com/nsn/3110-01-212-5246>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

Hollow

Overall Length:

Between 3.3250 inches and 3.4050 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Overall Outside Diameter:

Between 1.3000 inches and 1.3500 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.3250 inches and 0.3400 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

Between 2.0250 inches and 2.0550 inches

Shank Bore Diameter:

Between 0.4270 inches and 0.4470 inches

Shank Bore Depth:

1.0000 inches

Seal Quantity:

1

Shield Quantity:

1

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Internal Fit-up Designation:

Standard

Self-alignment Location:

Internal

Self-alignment Angle:

10.00 degrees

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp 4620 rod end body

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Single row, concave rollers

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.