

View Online at <https://aerobasegroup.com/nsn/3110-01-213-0978>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.4220 inches

Overall Length:

1.5215 inches

Overall Outside Diameter:

1.0000 inches

Lubrication Material:

Grease

Stud Diameter:

0.4370 inches

Outer Ring Width:

0.5310 inches

Stud Length:

0.9845 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Internal Fit-up Designation:

Standard

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

20

Thread Size:

0.4375 inches

Standard Tolerance Designation:

Afbma standard tolerance for can follwer needle bearing

Special Features:

End plate hardened torc 51.0 min to rc 59.0 max, raceway heat treated to rc 60.0 min, core and studlg heat treated to rc 36.0 min to rc 44.0 max; lubricator in flanged end of stud

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel end plate

Material Specification:

Sae assn standard single material response stud

Surface Treatment:

Cadmium exposed surfaces of stud and washer as mounted

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response exposed surfaces of stud and washer as mounted

Style Designator:

Cam follower

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.