

View Online at <https://aerobasegroup.com/nsn/3110-01-215-9862>

**Cross Sectional Shape:**

Counterbored w/ aperture

**Counterbore Diameter:**

Between 0.255 inches and 0.275 inches

**Counterbore Depth:**

0.050 inches

**Outside Diameter:**

1.500 inches

**Minor Thickness:**

Between 0.093 inches and 0.103 inches

**Mounting Hole Diameter:**

Between 0.167 inches and 0.174 inches

**Aperture Diameter:**

Between 0.268 inches and 0.271 inches

**Mounting Hole Arrangement Style:**

Single bolt hole circle

**Bolt Circle Hole Quantity:**

4

**Overall Thickness:**

0.165 inches

**Mounting Bolt Circle Diameter:**

1.125 inches

**Width Across Flats:**

1.188 inches

**Features Provided:**

Bolt

**Counterbore Diameter:**

Between 0.610 inches and 0.630 inches

**Counterbore Depth:**

Between 0.057 inches and 0.062 inches

**Mounting Hole Type:**

Round, unthreaded, counterbored

**Special Features:**

P/n 2533402-0016, nut, self locking, clinch through aperture, steel with red nylon 101 locking insert

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

**Material Specification:**

Aisi assn standard all material responses

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Dod-p-16232 military specification single treatment response

**Style Designator:**

Two flats

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A093a0

**Mil-std (military Standard):**

spec.