

View Online at <https://aerobasegroup.com/nsn/3110-01-215-9862>

Cross Sectional Shape:

Counterbored w/ aperture

Counterbore Diameter:

Between 0.255 inches and 0.275 inches

Counterbore Depth:

0.050 inches

Outside Diameter:

1.500 inches

Minor Thickness:

Between 0.093 inches and 0.103 inches

Mounting Hole Diameter:

Between 0.167 inches and 0.174 inches

Aperture Diameter:

Between 0.268 inches and 0.271 inches

Mounting Hole Arrangement Style:

Single bolt hole circle

Bolt Circle Hole Quantity:

4

Overall Thickness:

0.165 inches

Mounting Bolt Circle Diameter:

1.125 inches

Width Across Flats:

1.188 inches

Features Provided:

Bolt

Counterbore Diameter:

Between 0.610 inches and 0.630 inches

Counterbore Depth:

Between 0.057 inches and 0.062 inches

Mounting Hole Type:

Round, unthreaded, counterbored

Special Features:

P/n 2533402-0016, nut, self locking, clinch through aperture, steel with red nylon 101 locking insert

Material:

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

Material Specification:

Aisi assn standard all material responses

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Dod-p-16232 military specification single treatment response

Style Designator:

Two flats

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

spec.