

View Online at <https://aerobasegroup.com/nsn/3110-01-218-1566>

Cross Sectional Shape:

Raised surface w/ aperture

Outside Diameter:

6.750 inches

Minor Thickness:

0.140 inches

Aperture Diameter:

2.400 inches

Mounting Hole Arrangement Style:

Vertical centerline

Distance Between Holes Along Width:

6.000 inches

Overall Thickness:

1.090 inches

Countersink Diameter:

Between 0.400 inches and 0.440 inches

Raised Surface Height:

Between 0.390 inches and 0.430 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

Between 70.0 brinell standard and 90.0 brinell standard

Thread Size:

0.375 inches

Countersink Angle:

Between 85.0 degrees and 95.0 degrees

Counterbore Diameter:

5.000 inches

Distance From Horizontal Centerline To Center Of Lower Hole:

3.000 inches

Counterbore Depth:

1.500 inches

Mounting Hole Type:

Round, threaded, countersunk

Inside Raised Surface Diameter:

Between 3.0570 inches and 3.0585 inches

Outside Raised Surface Diameter:

Between 5.125 inches and 5.126 inches

Special Features:

Reduced od of flange to 2.770 in. R, upper right quadrant; six recessed slots in front face of raised surface; twelve 0.414 in. Diameter through holes in flange, unequally spaced on 6.000 in. Diameter bolt circle

Material:

Aluminum alloy 355.0

Material Specification:

Sae j453, grade 322-t71 assn standard single material response

Style Designator:

Round

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A093a0