

View Online at <https://aerobasegroup.com/nsn/3110-01-237-5328>

Cross Sectional Shape:

Raised surface w/ aperture

Minor Thickness:

Between 0.930 inches and 0.940 inches

Length:

4.500 inches

Mounting Hole Diameter:

Between 0.179 inches and 0.185 inches

Aperture Diameter:

1.894 inches

Mounting Hole Arrangement Style:

Four holes

Distance Between Holes Along Length:

3.500 inches

Distance Between Holes Along Width:

3.500 inches

Overall Thickness:

Between 1.745 inches and 1.755 inches

Raised Surface Height:

1.375 inches

Counterbore Diameter:

Between 2.0635 inches and 2.0645 inches

Distance From Vertical Centerline To Center Of Right Hole:

1.750 inches

Counterbore Depth:

Between 0.406 inches and 0.410 inches

Distance From Horizontal Centerline To Center Of Right Hole:

1.750 inches

Mounting Hole Type:

Round, unthreaded

Inside Raised Surface Diameter:

Between 2.0635 inches and 2.0645 inches

Outside Raised Surface Diameter:

0.407 inches

Special Features:

One 0.156 in. Diameter min to 0.160 in. Diameter maximum blind hole in outer face, 0.190 in. Dp, countersunk 0.187 in. Diy by 100.0 deg, w/one ms16562 tubular pin spring inserted, located 0.812 in. Below horiz cl and 1.312 in. Left of vert cl

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t651 federal specification single material response

Surface Treatment:

Enamel outer face as mounted

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response raised surface

Style Designator:

Square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A093a0

Mil-std (military Standard):

Mil-c-5541 spec.