

View Online at <https://aerobasegroup.com/nsn/3110-01-237-5328>

**Cross Sectional Shape:**

Raised surface w/ aperture

**Minor Thickness:**

Between 0.930 inches and 0.940 inches

**Length:**

4.500 inches

**Mounting Hole Diameter:**

Between 0.179 inches and 0.185 inches

**Aperture Diameter:**

1.894 inches

**Mounting Hole Arrangement Style:**

Four holes

**Distance Between Holes Along Length:**

3.500 inches

**Distance Between Holes Along Width:**

3.500 inches

**Overall Thickness:**

Between 1.745 inches and 1.755 inches

**Raised Surface Height:**

1.375 inches

**Counterbore Diameter:**

Between 2.0635 inches and 2.0645 inches

**Distance From Vertical Centerline To Center Of Right Hole:**

1.750 inches

**Counterbore Depth:**

Between 0.406 inches and 0.410 inches

**Distance From Horizontal Centerline To Center Of Right Hole:**

1.750 inches

**Mounting Hole Type:**

Round, unthreaded

**Inside Raised Surface Diameter:**

Between 2.0635 inches and 2.0645 inches

**Outside Raised Surface Diameter:**

0.407 inches

**Special Features:**

One 0.156 in. Diameter min to 0.160 in. Diameter maximum blind hole in outer face, 0.190 in. Dp, countersunk 0.187 in. Diy by 100.0 deg, w/one ms16562 tubular pin spring inserted, located 0.812 in. Below horiz cl and 1.312 in. Left of vert cl

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t651 federal specification single material response

**Surface Treatment:**

Enamel outer face as mounted

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response raised surface

**Style Designator:**

Square

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A093a0

**Mil-std (military Standard):**

Mil-c-5541 spec.