

View Online at <https://aerobasegroup.com/nsn/3110-01-239-8905>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.2500 inches

Overall Length:

Between 0.9790 inches and 1.0470 inches

Overall Outside Diameter:

Between 0.4990 inches and 0.5000 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.1900 inches and 0.1910 inches

Outer Ring Width:

Between 0.3700 inches and 0.3750 inches

Stud Length:

Between 0.6090 inches and 0.6410 inches

Internal Clearance:

0.0023 inches radial

Thready Qty Per Inch (tpi):

32

Thread Size:

0.191 inches

Standard Tolerance Designation:

Afbma standard tolerance for can follwer needle bearing

Special Features:

All external surfaces except the unthreaded portion of stud shank cadmium plated per qq-p-416, type 1, class 2, 0.0003 min thickness

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel stud or steel comp 8620 stud

Surface Treatment:

Chromium outer ring

Surface Treatment Specification:

Qq-c-320, class 2 federal specification single treatment response outer ring

Style Designator:

Cam follower

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.