

View Online at <https://aerobasegroup.com/nsn/3110-01-248-6246>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Diameter:

Between 0.3650 inches and 0.3850 inches

Shank Style:

Internally threaded

Overall Length:

Between 1.7455 inches and 1.7855 inches

Bore Diameter:

0.1897 inches

Overall Outside Diameter:

Between 0.7710 inches and 0.7910 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 0.7188 inches and 0.7812 inches

Outer Ring Width:

Between 0.3180 inches and 0.3380 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 1.3650 inches and 1.3850 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Self-alignment Angle:

10.00 degrees

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel

Material Specification:

Mil-s-7420 military specification single material response inner ring

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response rod end body

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.