

View Online at <https://aerobasegroup.com/nsn/3110-01-259-3698>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.2500 inches

Shank Style:

Externally threaded

Overall Length:

2.1980 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Lubrication Material:

Grease

Shank Thread Length:

0.9400 inches

Outer Ring Width:

Between 0.3450 inches and 0.3600 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

Between 1.6730 inches and 1.7030 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Furnished with 2 grease fittings; nas559 keyway in shank

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp 4620 rod end body

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Specification Data:

81205-bacb10de manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.