

View Online at <https://aerobasegroup.com/nsn/3110-01-274-1394>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.3440 inches

Overall Length:

1.0150 inches

Overall Outside Diameter:

Between 0.4995 inches and 0.5010 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.1885 inches and 0.1900 inches

Outer Ring Width:

Between 0.2760 inches and 0.2810 inches

Stud Length:

Between 0.7030 inches and 0.7500 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Cotter pin hole in threaded end of stud, 0.100 in. From stud end, 0.070 in. Dia; no lubrication

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100 stud

Surface Treatment:

Cadmium exposed surfaces as mounted

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response exposed surfaces as mounted

Style Designator:

Cam follower

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.