

View Online at <https://aerobasegroup.com/nsn/3110-01-294-0377>

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.9009 inches and 0.9014 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.3300 inches and 0.3350 inches

Inner Ring Width:

Between 0.4790 inches and 0.4840 inches

Seal Quantity:

2

Bearing Seal Type:

One lip inward, one lip outward

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Internal Clearance:

0.0006 inches radial and 0.0014 inches radial

Lubrication Material Specification:

Mil-g-2387 military specification single material response

Material:

Steel comp e52100 inner racesteel comp e52100 outer racesteel comp e52100 rollerrubber butadiene-acrylonitrile class nbr sealsteel comp 430 shield

Material Specification:

Mil-s-7420 military specification single material response inner racemil-s-7420 military specification single material response outer racemil-s-7420 military specification single material response rollerqq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416a, type 1, class 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Concave roller, double closure, self aligning

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-2387 spec.