

View Online at <https://aerobasegroup.com/nsn/3110-01-296-5388>

Thread Class:

3a

Thread Pitch Diameters:

+0.3394/+0.3425 inches

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded w/slot

Overall Length:

3.1000 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Lubrication Material:

Grease

Shank Thread Length:

1.3750 inches

Outer Ring Width:

Between 0.4430 inches and 0.4530 inches

Inner Ring Width:

Between 0.8070 inches and 0.8120 inches

Length From Bore Center To Shank End:

2.3500 inches

Retainer Fabrication Method:

Pressed

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Internal Clearance:

0.0000 inches radial and 0.0010 inches radial

Thready Qty Per Inch (tpi):

20

Thread Size:

0.3750 inches

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Stainless steel retainer

Material Specification:

Fed-std-66 federal standard single material response ball

Surface Treatment:

Cadmium inner race bore

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response inner ring

Style Designator:

Double row, staggered, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.