

View Online at <https://aerobasegroup.com/nsn/3110-01-314-8538>

Cross Sectional Shape:

Raised surface w/ aperture

Counterbore Diameter:

Between 0.350 inches and 0.410 inches

Counterbore Depth:

Between 0.080 inches and 0.100 inches

Outside Diameter:

Between 2.410 inches and 2.470 inches

Minor Thickness:

Between 0.240 inches and 0.260 inches

Mounting Hole Diameter:

Between 0.210 inches and 0.218 inches

Mounting Hole Arrangement Style:

Four holes

Overall Thickness:

1.560 inches

Width Across Flats:

Between 1.910 inches and 1.970 inches

Raised Surface Height:

Between 0.105 inches and 0.110 inches

Counterbore Diameter:

Between 0.863 inches and 0.865 inches

Distance From Vertical Centerline To Center Of Right Hole:

0.685 inches

Counterbore Depth:

Between 0.090 inches and 0.150 inches

Distance From Horizontal Centerline To Center Of Right Hole:

0.695 inches

Mounting Hole Type:

Round, unthreaded, counterbored

Inside Raised Surface Diameter:

Between 1.240 inches and 1.260 inches

Outside Raised Surface Diameter:

Between 1.548 inches and 1.550 inches

Material:

Aluminum alloy 6061

Material Specification:

Astm b211, t6 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 3, class 1 military specification single treatment response

Style Designator:

Two flats

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

Mil-a-8625 spec.