

View Online at <https://aerobasegroup.com/nsn/3110-01-314-9119>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

651 externally threaded

Overall Length:

2.6400 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.2600 inches and 1.3200 inches

Outer Ring Width:

Between 0.3450 inches and 0.3600 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

2.1000 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

45.00 degrees

Special Features:

Grease fitting per nas 516-1

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp 4620 rod end body

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.