

View Online at <https://aerobasegroup.com/nsn/3110-01-323-8091>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.4995 inches

Bore Diameter:

Between 0.2495 inches and 0.2505 inches

Overall Outside Diameter:

Between 0.8650 inches and 0.8850 inches

Lubrication Material:

Grease

Shank Thread Length:

1.5000 inches

Outer Ring Width:

Between 0.3300 inches and 0.3400 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 2.0520 inches and 2.0720 inches

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

24

Thread Size:

0.3750 inches

Lubrication Material Specification:

Mil-g-81322 military specification single material response or mil-g-23827 military specification single material response

Material:

Steel comp e52100 ball

Material Specification:

Mil-s-7420 military specification single material response ball or ams 7440 assn standard single material response ball

Surface Treatment:

Chromium ball

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response rod end body

Style Designator:

Single row, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.