

View Online at <https://aerobasegroup.com/nsn/3110-01-344-0660>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.7500 inches

Overall Length:

1.8910 inches

Overall Outside Diameter:

Between 1.2480 inches and 1.2500 inches

Stud Diameter:

Between 0.5000 inches and 0.5010 inches

Outer Ring Width:

Between 0.7450 inches and 0.7500 inches

Stud Length:

Between 1.0940 inches and 1.1560 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.5000 inches

Special Features:

Prepack with mil-g-23827 grease; lubricator in threaded end, slotted stud

Material:

Steel comp e52100 end plate or steel comp 1095 end plate steel comp e52100 outer ring steel comp e52100 roller steel comp 8720h stud or steel comp 8620h stud or steel comp 4620h stud

Material Specification:

Mil-s-7420 military specification 1st material response end plate or astm a108 assn standard 2nd material response end plate mil-s-7420 military specification single material response outer ring mil-s-7420 military specification single material response roller or 66 federal standard single material response roller astm a304 assn standard all material responses stud

Surface Treatment:

Cadmium exposed surfaces as mounted and chromate exposed surfaces as mounted chromium outer ring outside diameter chromium outer ring sides

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response exposed surfaces as mounted qq-c-320, cl 2 federal specification single treatment response outer ring outside diameter qq-c-320, cl 2 federal specification single treatment response outer ring sides

Style Designator:

Cam follower

Thread Series Designator:

Unf

Specification Data:

81205-bacb10b manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Fig:

A044a0

Mil-std (military Standard):

Mil-s-7420 spec.