

View Online at <https://aerobasegroup.com/nsn/3110-01-347-7001>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.3590 inches

Overall Length:

2.3500 inches

Overall Outside Diameter:

Between 0.8745 inches and 0.8760 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.3735 inches and 0.3750 inches

Outer Ring Width:

Between 0.4640 inches and 0.4690 inches

Stud Length:

1.8590 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

24

Thread Size:

0.3750 inches

Standard Tolerance Designation:

Afbma standard tolerance for can follwer needle bearing

Special Features:

Cotter pin hole in stud 0.10 in. From stud end; 0.106 in dia

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel end platesteel comp e52100 outer ringsteel comp e52100 rollerplastic acetal seal or plastic polyamide sealsteel comp e52100 stud

Material Specification:

Sae assn standard single material response outer ringsae assn standard single material response rollersae assn standard single material response stud

Surface Treatment:

Cadmium end platechromium outer ringcadmium stud

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response end plateqq-c-320, cl 2 federal specification single treatment response outer ringqq-p-416, type 1, cl 2 federal specification single treatment response stud

Style Designator:

Cam follower

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.