

View Online at <https://aerobasegroup.com/nsn/3110-01-355-1001>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.4220 inches

Overall Length:

2.1100 inches

Overall Outside Diameter:

Between 1.1245 inches and 1.1260 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.4985 inches and 0.5000 inches

Outer Ring Width:

Between 0.6510 inches and 0.6560 inches

Stud Length:

Between 1.7810 inches and 1.8280 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Special Features:

Lubricator in flanged end of stud

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel end platesteel comp e52100 outer ringsteel comp e52100 rollerplastic acetal shell or plastic polyamide shellsteel comp e52100 stud

Material Specification:

Sae assn standard single material response outer ringsae assn standard single material response rollersae assn standard single material response stud

Surface Treatment:

Cadmium end plate and chromate end platechromium outer ringcadmium stud and chromate stud

Surface Treatment Specification:

Qq-p-416, ty1, cl2 federal specification single treatment response end plateqq-c-320, cl2 federal specification single treatment response outer ringqq-p-416, ty1, cl2 federal specification single treatment response stud

Style Designator:

Cam follower

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Specification Data:

80205-nas562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.