

View Online at <https://aerobasegroup.com/nsn/3110-01-359-9477>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

659 hollow

Overall Length:

2.4300 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

1.0800 inches

Outer Ring Width:

Between 0.3450 inches and 0.3600 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 1.8600 inches and 1.8900 inches

Shank Bore Diameter:

Between 0.3650 inches and 0.3850 inches

Shank Bore Depth:

1.0430 inches

Seal Quantity:

1

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

External

Self-alignment Angle:

10.00 degrees

Special Features:

Drilled hole filled with narmco putty no.3119 or hysol 2204 resin

Material:

Steel comp e52100 inner racesteel comp 4620 rod end body or steel comp 8620 rod end bodysteel comp e52100 rollerplastic polytetrafluoroethylene sealsteel comp 430 shield

Material Specification:

Mil-s-7420 military specification single material response inner raceams 6294 assn standard single material response rod end body or ams 6274 assn standard single material response rod end bodymil-s-7420 military specification single material response rollerqq-s-766 federal specification single material response shield

Style Designator:

Single row, concave rollers

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-s-7420 spec.