

View Online at <https://aerobasegroup.com/nsn/3110-01-362-9812>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded

Overall Length:

Between 2.3700 inches and 2.3900 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 0.9800 inches and 1.0020 inches

Outer Ring Width:

0.3750 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 1.8300 inches and 1.8500 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Internal clearance 0.0002 in. Min 0.0010 in. Max; keyway in shank

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp e52100 inner ringsteel comp e52100 rollerplastic polytetrafluoroethylene sealsteel comp 4620 supporting sleeve or steel comp 4130 supporting sleeve or steel comp 8620 supporting sleeve or steel comp e52100 supporting sleeve

Surface Treatment:

Cadmium exposed surfaces as mounted

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.