

View Online at <https://aerobasegroup.com/nsn/3110-01-422-8045>

Shank Diameter:

Between 0.4980 inches and 0.5000 inches

Shank Style:

659 hollow

Overall Length:

3.3190 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.3250 inches and 0.3400 inches

Inner Ring Width:

Between 0.5530 inches and 0.5580 inches

Length From Bore Center To Shank End:

Between 2.6300 inches and 2.6600 inches

Shank Bore Diameter:

0.3750 inches

Shank Bore Depth:

1.0500 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Special Features:

Reduced internal fit; two lube fittings

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.