

View Online at <https://aerobasegroup.com/nsn/3110-01-465-3321>

**Bore Diameter:**

Between 0.9995 inches and 1.0000 inches

**Overall Outside Diameter:**

Between 1.7495 inches and 1.7500 inches

**Lubrication Material:**

Grease

**End Application:**

Helicopter, lamps mark iii, sh-60b

**Outer Ring Width:**

Between 0.3700 inches and 0.3750 inches

**Inner Ring Width:**

Between 0.4345 inches and 0.4370 inches

**Alignment Type:**

Self-aligning

**Load Direction:**

Radial

**Self-alignment Location:**

Internal

**Internal Clearance:**

0.0001 inches radial and 0.0005 inches radial

**Product Name:**

Precision bearing radial torque tube type

**Lubrication Material Specification:**

Mil-g-81322 military specification 1st material response

**Material:**

Steel comp e52100 outer ring

**Material Specification:**

Ams6440 assn standard single material response ball or ams6444 assn standard single material response ball

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification 1st treatment response

**Style Designator:**

Single row, torque tube type, w/or w/o closure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-g-81322 spec.