

View Online at <https://aerobasegroup.com/nsn/3120-00-001-4759>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/bead and wrench flats and inspection hole

Overall Length:

1.8657 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Outer Member Outside Diameter:

Between 0.7710 inches and 0.8160 inches

Bore Center To Shank End Distance:

Between 1.4590 inches and 1.4790 inches

Outer Member Width:

Between 0.3320 inches and 0.3420 inches

Inner Member Width:

Between 0.4350 inches and 0.4370 inches

Shank Thread Length:

Between 0.7200 inches and 0.8100 inches

Inspection Hole Center To End Distance:

Between 0.3650 inches and 0.3950 inches

Shank Width Across Wrench Flats:

Between 0.4270 inches and 0.4470 inches

Static Radial Load Rating:

4400 pounds

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Lubricant on spherical surface of race insert only

Material:

Steel comp 630 rod end body

Surface Treatment:

Chromium inner member

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0