

View Online at <https://aerobasegroup.com/nsn/3120-00-001-8164>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.6875 inches

Bore Diameter:

Between 0.4370 inches and 0.4375 inches

Outer Member Outside Diameter:

1.1250 inches

Bore Center To Shank End Distance:

Between 2.0650 inches and 2.1850 inches

Outer Member Width:

Between 0.4320 inches and 0.4370 inches

Inner Member Width:

Between 0.5570 inches and 0.5620 inches

Shank Thread Length:

Between 1.3150 inches and 1.4350 inches

Static Radial Load Rating:

15700 pounds

Thread Diameter:

0.500 inches

Features Provided:

Flush lubrication fitting

Thready Qty Per Inch (tpi):

20

Hardness Rating:

59.0 rockwell c inner member and 63.0 rockwell c inner member

Lubrication Feature:

Groove internal outer member

Special Features:

Nas559 keyway in shank

Material:

Steel comp 4130 rod end body

Surface Treatment:

Cadmium rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0